

Phelps Honey Wagon, Inc.



PHW 300M

- Pump:** Pump is self-priming flexible impeller with stainless steel wearplates
Macerator's stainless steel cutter reduces particle size to 1/8 in. maximum
Inlet port for the 3 in. slip on hose
Outlet port for 50 ft. x 1 in. OD Pressure Hose
- Motor:** 115 Vac, single phase, 60 Hz, thermal overload protection
- Tank:** 300 Gallon Capacity Tank
Polyethylene elliptical plastic tank for long life with approx. 1/4 in. walls
Dimensions: 48 in. width | 32 in. height | 70 in. length
Translucent tank to show content level
Tank is supported by a steel pan on a 5 in. steel channel frame
Large top lid for easy interior hose down
- Discharge:** Gravity drain with 3 in. rear discharge gate valve and cap
- Adapters:** RV Hose Adapter, fits all RV's
- Tongue:** 2 in. ball coupler
Side Wind Jack with Wheel (800 lbs. maximum)
- Axle:** Single axle - 3500 lbs. rating
- Tires:** 175/80-13" tires
- Weight:** Pump and Motor: approx. 17 lbs. [Must be carried to RV]
Wagon: approx. 500 lbs
- Warranty:** One year warranty on trailer and tank
One year warranty on pump and motor, except for wearable parts

158 Whiskey Springs Road
Dillsburg, PA 17019

Phone: 1-800-463-3707

www.phelphoneywagon.com