



# *Phelps Honey Wagon, Inc*

## **Specs for 300E (Electric)**

---

**Pump**                    Cast aluminum pump to resist corrosion  
12 in. Thermoplastic Diaphragm  
50 gallons per minute  
Will pump a 25 ft. head  
Neoprene Flapper Valves  
Self-priming

**Motor**                    1.5 H.P. single phase, 115/230-volt electric motor with manual reset overload  
Weatherproof on/off switch  
20 foot 115 VAC power cord

**Tank**                     300 Gallon Capacity Tank  
Polyethylene elliptical plastic tank for long life with approx. 1/4 in. walls  
Dimensions: 48 in. width | 32 in. height | 70 in. length  
Translucent tank to show content level  
Tank is supported by a steel pan on a 5 in. steel channel frame  
Large top lid for easy interior hose down

**Discharge**             Gravity drain with 3 in. rear discharge gate valve and cap

**Adapters**                RV Hose Adapter, fits all RV's

**Hose**                     50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking

**Tongue**                 2 in. ball coupler  
Side Wind Jack with Wheel (800 lbs. maximum)

**Axle**                     Single axle – 3500 lbs. rating

**Tires**                    175/80-13" tires

**Weight**                 Approx. 840 lbs

**Warranty**                The tank and trailer have a two year limited warranty.  
The diaphragm pump has a two year warranty, except for wearable parts  
The hoses and adapters have a 60 day warranty.