

Phelps Honey Wagon, Inc Specs for 300GH EXT (Gas - Honda)

Pump Cast aluminum pump to resist corrosion

12 in. Nylon Reinforced Diaphragm

50-60 gallons per minute Will pump a 25 ft. head Polyurethane Flapper Valves

Self-priming

Blue Water Pump Honda Driven Water pump 30 gallons per minute / 45 psi

Motor

GX160 Honda Engine

Tank

300 Gallon Capacity Tank

Polyethylene elliptical plastic tank for long life with approx. 1/4 in. walls

Dimensions: 48 in. width | 32 in. height | 70 in. length

Translucent tank to show content level

Tank is supported by a steel pan on a 5 in. steel channel frame

Large top lid for easy interior hose down

Blue Water Tank

125 Gallon Capacity Tank

Same great properties as the 300 gallon tank

Discharge

Gravity drain with 3 in. rear discharge gate valve and cap

Adapters

Pit Adapter or RV Hose Adapter

Hose

50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking

Tongue

2 in. ball coupler

Side Wind Jack with Wheel (1000 lbs. maximum)

Axle

Single axle - 3500 lbs. rating

Tires

2 ST175/80 D 13" tires with electric brakes

Weight

Approx. 1250 lbs

Warranty

The tank and trailer have a two year limited warranty.

The diaphragm pump has a two year warranty, except for wearable parts

The hoses and adapters have a 60 day warranty.