



Phelps Honey Wagon, Inc

Specs for 500GH

Pump	Cast aluminum pump to resist corrosion 12 in. Thermoplastic Diaphragm 60 gallons per minute Will pump a 25 ft. head Neoprene Flapper Valves Self-priming
-------------	---

Motor	GX160 Honda engine
--------------	--------------------

Tank	500 Gallon Capacity Tank Polyethylene plastic tank for long life with approx. 1/4 in. walls Dimensions: 48 in. diameter 75 in. length Translucent tank to show content level Tank is supported by a steel pan on a 5 in. steel channel frame Large top lid for easy interior hose down
-------------	---

Discharge	Gravity drain with 3 in. rear discharge gate valve and cap
------------------	--

Adapters	RV Hose Adapter, fits all RV's
-----------------	--------------------------------

Hose	50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking
-------------	--

Tongue	2 in. ball coupler
---------------	--------------------

Axle	Tandem axle – 3500 lbs. rating per axle
-------------	---

Tires	175/80-13" tires
--------------	------------------

Weight	Approx. 1090 lbs
---------------	------------------

Warranty	The tank and trailer have a two year limited warranty. The diaphragm pump has a two year warranty, except for wearable parts The hoses and adapters have a 60 day warranty.
-----------------	---