



Phelps Honey Wagon, Inc

Specs for 500E

Pump Cast aluminum pump to resist corrosion
12 in. Thermoplastic Diaphragm
40-50 gallons per minute
Will pump a 25 ft. head
Neoprene Flapper Valves
Self-priming

Motor 1.5 H.P. single phase, 115/230-volt electric motor with manual reset overload
Weatherproof on/off switch
20 foot 115 VAC power cord

Tank 500 Gallon Capacity Tank
Polyethylene plastic tank for long life with approx. 1/4 in. walls
Dimensions: 48 in. diameter | 75 in. length
Translucent tank to show content level
Tank is supported by a steel pan on a 5 in. steel channel frame
Large top lid for easy interior hose down

Discharge Gravity drain with 3 in. rear discharge gate valve and cap

Adapters RV Hose Adapter, fits all RV's

Hose 50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking

Tongue 2 in. ball coupler

Axle Tandem axle – 3500 lbs. rating per axle

Tires 175/80-13" tires

Weight Approx. 1090 lbs

Warranty The tank and trailer have a two year limited warranty.
The diaphragm pump has a two year warranty, except for wearable parts
The hoses and adapters have a 60 day warranty.